



GU10 Down Light 9w WW

| | |
|------------------------------|---|
| Product Codes | GU10-9w3ww |
| Lamp cap | GU10 |
| Power Consumption (w) | 8.5w |
| Operating voltage | 85-265v |
| Power Factor | 0.55Pf |
| Chip Type & Count | 3 x 3w HP |
| Colour temperature | 2900k WW |
| Light output (lumens) | 600 (ww) |
| Rated LED life (hours) | 50000 |
| Colour rendering index (CRI) | >80 |
| Beam angle (degrees) | 60° |
| Dimming Range | Non-dimmable |
| IP Rating | IP30 |
| Operating Temp | -10° - 60°C |
| Max Humidity | 85% |
| Replaces : Halogen | 60w |
| : CFL | |
| Warranty (months) | 6 |
| Certification | CE, Eskom, NRCS & RoHS |
| Dimensions (L x B x H) | 49.8 x 49.8 x 81mm (67/69g) |
| Materials | PBT Thermoplastic Casing, Aluminium Cooler, Polycarbonate Lens |
| Applications | These medium beam angle down lights medium to high ceilings high over counters in front of cabinets good spotlights. These lights but not in bathrooms |
| Limitations | These down lights are not recommended for ceilings above 4m and not suitable for dimming |
| Other Features | The reduced length base allows these cost effective versatile globe to be used in standard GU10 halogen fittings and other restricted length environments without fitting adjustment or modification. A bleed resistor is not required when using this globe with two way switches. |
| Compatible Dimmers | Not dimmable |
| Similar Products | A cheaper alternative to this globe is available (pg 24) |
| Complementary Products | Downlight fittings (pg 30), lamp holders (pg 30) |
| Customer Price | See Main Items Price List line 97 for pricing |

Customer Notes

